



Product Feature

- Global universal voltage: 90-264VAC 50/60Hz
- Pin: CN, EU, US, UK, AU standard
- Operating temperature range: -20°C to +40°C
- Output short circuit, overcurrent, and over temperature protection
- High efficiency and reliability
- Stable voltage output, low ripple noise
- Size: 45 x 40 x 27.5 mm ± 0.5MM
- 1-year warranty



This series of power supplies has the advantages of global input voltage range, low power consumption, high efficiency, high reliability, and safe isolation. The product is safe and reliable, with good EMC performance. The EMC and safety specifications meet the IEC/EN6100-4, CISPR32/EN5032, and UL/EN/IEC62368 standards. This series of products is widely used in industries such as network equipment, office equipment, small appliances, and electronic products. When applied in environments with poor electromagnetic compatibility, reference must be made to the application circuit.

Model Selection Table

Certificate	Model Number	Power output	Nominal output voltage and current (Vo/Io)	Efficiency (230VAC/%, Typ.)	Maximum Load (A)
CE FCC ROHS UKCA ERP	GHY-050100	5.0W	5V/1.0A	≥73.62	1.0
	GHY-050150	7.5W	5V/1.5A	≥76.65	1.5
	GHY-050200	10.0W	5V/2.0A	≥78.70	2.0
	GHY-050240	12.0W	5V/2.4A	≥79.94	2.4
	--	--	--	--	--
	--	--	--	--	--
	--	--	--	--	--

Input characteristics

Item	Working conditions	Min.	Typ.	Max.	unit
Input Voltage	AC input	90	--	264	VAC
Input frequency		47	--	63	Hz
Input Current	115VAC	--	--	250	mA
	230VAC	--	--	150	
Impulse current	115VAC	--	35	--	A
	230VAC	--	50	--	
hot plugging				Support	

Output characteristics

Item	Working conditions	Min.	Typ.	Max.	unit
Voltage accuracy	Full load	--	±5	--	%
Load regulation rate		--	±5	--	
Ripple noise*	20MHz Bandwidth (peak to peak)	--	--	150	mV
Standby power		--	--	0.1	W
Temperature coefficient		--	±0.02	--	%/°C
Short circuit protection					Hiccup type, capable of long-term short circuit and self recovery
Overcurrent protection					≥120% Io, self recovery
Over Temperature Protection		0	≥40	--	°C
Power-off protection time	230VAC input	--	35	--	ms

Note: The testing method for ripple and noise adopts the parallel line testing method. For specific operation methods, please refer to the "Application Guide for AC-DC Switching Power Supply".



General characteristics

item	Working conditions	Min.	Typ.	Max.	unit
Isolation voltage input-output	Test time 1 minute, leakage current<5 mA	3000	--	3750	VAC
Operation temperature		-20	--	+40	°C
Storage temperature		-25	--	+65	
Storage humidity		--	--	90	%RH
Switching frequency		--	65	--	kHz
Power derating	-20°C to -10°C	2.0	--	--	%/°C
	+30°C to +40°C	2.5	--	--	
	90VAC - 100VAC	0.375	--	--	%/VAC
	240VAC - 264VAC	0.833	--	--	
Safety standards	Passed: EN IEC 62368-1: 2020+A11: 2020 GB 4943. 1-2022 Conforms to: GB/T 9254. 1-2021 GB 17625. 1-2022 UL/IEC62368-1 & BS EN 62368-1				
MTBF				MIL-HDBK-217F@25°C >30,000 h	

EMC characteristics

EMI	Conducted Disturbance	CISPR32/EN55032	CLASS B	
	Radiated Disturbance	CISPR32/EN55032	CLASS B	
EMS	Electrostatic Discharge	IEC/EN61000-4-2	Contact ±6KV	Perf. Criteria B
	Radiated immunity	IEC/EN61000-4-3	10V/m	Perf. Criteria A
	Pulse group immunity	IEC/EN61000-4-4	±2KV	Perf. Criteria B
	Surge immunity	IEC/EN61000-4-5	line to line ±1KV	Perf. Criteria B
	Conducted disturbance immunity	IEC/EN61000-4-6	10Vr.m.s	Perf. Criteria A
	Voltage sag, drop, and short-term interruption immunity	IEC/EN61000-4-11	100% dip 1 periods, 30% dip 25 periods, 100% interruptions 250 periods	Perf. Criteria B

Product characteristic curve



Physical property

Shell size	45 x 40 x 27.5 mm ±0.5MM
Weight	44.5g(Typ.)
Cooling method	Natural air cooling

Characteristics of shell pins

Type	CN,EU,US,UK,AU standard
Plastic material	material, environmental protection, fire prevention
Pin hardware	Copper feet



CN



US



EU



AU




UK

DC plug specifications

Type	Standard USB-A*2
DC head specifications	--
length	--

母头



Note:

1. For more detailed parameter information, please contact the sales personnel.
2. All indicators in this manual are measured at $T_a=25^{\circ}\text{C}$, humidity<75%, nominal input voltage, and output rated load;
3. The testing methods for all indicators in this manual are based on our company's enterprise standards;
4. Our company can provide product customization, and specific requirements can be directly contacted by our technical personnel;

Contact information/联系方式

Manufacture: Shenzhen GHSOU Technology Co., Ltd

制造商: 深圳市广皓源科技有限公司

Website: www.ghsou.com 官网: www.ghy2012.com

Tel: +86-0755-23572580 手机: 13480623962 Email: gdhsou@126.com

地址: 深圳市光明区公明镇西田第三工业区24栋4-5楼

Add: Floor 4-5, Building 24, Xitian Third Industrial Zone, Gongming Town, Guangming District, Shenzhen, guangdong, China